

# FORMAX®

Div. of BESCORP, Inc.

## FD 500

### TABLETOP BURSTER

#### Standard Features

- **Adjustable Burst Bar:** Compensates for various paper sizes, weights, and perforations
- **Side Trimmers:** Easily adjustable slitters for side margin removal

#### Options:

- **Tractor Feed:** The optional tractor feed ensures accurate registration for multi-set bursting and trimming of critical documents such as checks.



The FD 500 heavy-duty Table Top Burster is a machine to meet almost any forms handling requirement. The FD 500 with side trimmers operates at 90 feet per minute, and can separate one to six-part forms.

#### Specifications:

Fixed Speed:	Up to 90 feet per minute
Form Size:	3" - 18" width 3" - 12" depth
Paper Weight:	10# up to 110#
Feeding System:	Friction feed
Stacker:	Receiving tray
Power:	110/120 volts 60 Hz
Weight:	88 lbs.
Dimensions:	36" L x 25" W x 9" H

## NEXXPOST

206-764-9000 1-800-910-7678  
[www.nexxpost.com](http://www.nexxpost.com)

**Formax a Division of Bescorp, Inc.**  
New Hampshire, USA  
Web Site: [www.formax.com](http://www.formax.com)

**LOCAL DEALER:**

# FORMAX®

Div. of BESCORP, Inc.

## FD 676

CONTINUOUS FORM  
INDUSTRIAL BURSTERS

### Standard Features

- **FD 676:** Tractor feed, slitters, and base
- **FD 680:** FD 676 with an imprinter

### Options:

- Center slitler
- Static eliminator
- Cylinders for 2-up printing
- Merger for 2-up forms
- Tri-color ink roll
- Vertical folder
- Power drop stacker
- Cover lock
- Photo-cell counter (6-digit)
- On/off key switch
- Crash imprinting
- Last form shut-off switch

**PAPER WEIGHT:** Up to 140 lb. card stock,  
up to 8 parts

## NEXXPOST

206-764-9000 1-800-910-7678  
[www.nexxpost.com](http://www.nexxpost.com)

**Formax a Division of Bescorp, Inc.**  
New Hampshire, USA  
Web Site: [www.formax.com](http://www.formax.com)

**LOCAL DEALER:**



FD 680

Three levels of performance are available to process continuous form documents. The Low-Volume Series processes at speeds of 0 to 200 feet per minute. The Medium-Volume Series processes at speeds of 15 to 350 feet per minute and is capable of handling up to 17" long forms. The High-Volume Series operates at speeds up to 500 feet per minute. All three Series offer a wide array of options to meet individual customer needs. The Low and Medium-Volume Series can be used up to five hours per day, five days a week. The High-Volume Series is capable of continuous operation, seven days a week.

### Specifications:

Speed:	Variable, 30 - 500 feet per minute
Form Size:	2 3/4" to 19 1/4" (slitting) width 2 3/4" to 17" (non-slitting) width 2 3/4" to 17" length
Power:	115 volts AC 50/60 Hz
Weight:	FD 676 & FD 680 - 428 lbs.
Dimensions:	58" L x 41" W x 56" H (with base)
Safety Certifications:	UL

## MEDIUM-VOLUME SERIES

### Standard Features:

- **FD 566:** Tractor feed, slitters, base
- **FD 666:** Tractor feed, slitters, base (17" maximum form length)
- **FD 668:** FD 666 with an imprinter

### Options:

- Imprinter, center slit
- Dust cover, tri-color ink roller
- Cylinder for 2-up printing
- Merger for 2-up forms
- Extra-wide margin trimmers
- Photo-cell counter (6-digit)
- Last form shut-off switch (666 & 668)
- Imprint modules, power drop stacker

**PAPER WEIGHT:** 100 lb. total, up to 4 parts  
(none exceeding 60 lb. tag stock)



FD 566

### Specifications:

Speed:	Variable, 15 - 350 feet per minute
Form Size:	2 3/8" - 16" width 2 3/4" - 12" length, up to 17" (FD 666 & 668)
Power:	115 volts AC 50/60 Hz
Weight:	193 lbs. (FD 566) 352 lbs. (FD 666 & 668)
Dimensions:	58" L x 41" W x 56" H (with base)
Safety Certifications:	UL

## LOW-VOLUME SERIES

### Standard Features:

- **FD 544:** Variable speed, friction feed
- **FD 546:** Variable speed, friction feed, slitters
- **FD 548:** FD 546 with base
- **FD 550:** Tractor feed, slitters and base
- **FD 552:** FD 550 with imprinter

### Options:

- Center slit, static eliminator
- Cylinders for 2-up printing
- Merger for 2-up forms, dust cover
- Tri-color ink roll, vertical folder
- Power drop stacker, cover lock
- Photo-cell counter (6-digit)

**PAPER WEIGHT:** 100 lb. total, up to 4 parts  
(none exceeding 60 lb. tag stock)



FD 550

### Specifications:

Speed:	Variable, 0 - 200 feet per minute
Form Size:	2 3/8" - 16" width 2 3/4" - 12" length
Power:	115 volts AC 50/60 Hz
Weight:	105 lbs. (FD 544) 88 lbs. (base)
Dimensions:	59" L x 32" W x 56.5" H (with base)
Safety Certifications:	UL

**Standard Features**

- Electronic Length Settings: Provide for quick and easy set-up
- Side Guides: Adjustable to different form widths
- Adjustable Feeding Pressure Lever: Accommodates different paper weights
- Operator-Friendly: Push-button controls feature start/stop, jog switch, and electronic tenth setting
- Top-loading feed system
- Examples:



One pass



Two passes

**Options:**

- Belt conveyor stacker: Provides neat, sequential stacking of burst forms



The FD 415 Cut Sheet Burster is the ideal finishing solution when multiple forms are printed on one page. Direct from a laser printer to the FD 415, pre-perforated forms are automatically burst at the perforation and stacked sequentially at speeds of up to 140 sheets per minute. No more cut sheet bursting by hand!

**Specifications:**

Speed:	90 or 140 sheets per minute
Form Size:	4" x 5" up to 11" x 17"
Paper Weight:	13# up to 110#
Bursting Length:	2.5 to 9.9 inches
Feed Tray Capacity:	400 sheets
Power:	120V, 0.8A
Dimensions:	32" L x 16" W x 9" H
Weight:	56 lbs.



**Formax a Division of Bescorp, Inc.**  
New Hampshire, USA  
Web Site: [www.formax.com](http://www.formax.com)

**LOCAL DEALER:**

# FORMAX®


Div. of BESCORP, Inc.

## FD 572 CUT SHEET CUTTER

### Standard Features

- User-Friendly Control Panel: Provides operator with helpful word prompts for effective and efficient operation
- 6 Pre-programmed Paper Cutting Sizes, including:
  - 8.5" into 1, 2, 3 or 4 even cuts
  - 11" into 1, 2, 3 or 4 even cuts
  - 14" into 1, 2, 3, 4 or 5 even cuts
- 100 Memory Selections: Available for custom cutting operations
- Cutting Method: Guillotine Cutter
- Top-loading feed system
- Counter: Keeps track of the number of forms fed, as well as the number of pieces cut
- Example:

One Pass:  
2 Vertical Cuts  
1 Perforation



### Options:

- Slitters
- Perforators
- Belt conveyor stacker: Provides neat, sequential stacking of burst forms



**Formax a Division of Bescorp, Inc.**  
New Hampshire, USA  
Web Site: [www.formax.com](http://www.formax.com)

### LOCAL DEALER:



Control Panel

The FD 572 Cut Sheet Cutter is designed to process up to 50 cut sheet forms, from non-impact or laser printers, per minute. The FD 572 will automatically feed the forms and cut, slit, or perforate in the desired position. This is ideal for use with checks, coupons, tickets, notices, membership cards and labels.

### Specifications:

Speed:	Up to 50 forms per minute
Form Size:	2.5" x 4" up to 16.5" x 18"
Paper Weight:	13# up to 110#
Minimum Cutting Length:	2"
Cutting Tolerance:	+ or - 1 mm
Feed Tray Capacity:	400 sheets (20# paper)
Power:	120 V, 60 Hz
Dimensions:	33" L x 23" W x 7" H
Weight:	90 lbs.

# FORMAX<sup>®</sup>

Div. of BESCORP, Inc.

## 590 Series

MULTI-STATION DECOLLATORS

### Standard Features

- **FD 592:** Two stations
- **Tractor Feed**
- **Margin Slitters**
- **Safety Jog Switches**

### Options:

- **FD 593:** Three stations
- **FD 594:** Four stations
- **FD 595:** Five stations
- **FD 596:** Six stations
- One-part add-on center slitter
- Paper control rod for carbonless forms



FD 594

### Continuous Form Decollators

Two models are available to process both carbon interleaved and carbonless multi-part forms. The two-part decollator is an easy-to-use floor model. Our multi-station decollator is capable of processing up to six-part forms clean, quickly and efficiently. The multi-station decollator offers the flexibility to add stations as applications grow.

### Specifications:

Speed:	Variable, 0 - 475 feet per minute
Form Size:	2 3/4" to 19" width (slitting) 2 3/4" to 17 7/8" width (non-slitting) Up to 14" length
Power:	115 volts AC 50/60 Hz
Weight:	FD 592: 235 lbs. 1-part add-on: 50 lbs.
Dimensions:	54" L x 30" W x 39" H (FD 592) Additional 13.5" L per 1-part add-on
Safety Certifications:	UL



**Formax a Division of Bescorp, Inc.**  
New Hampshire, USA  
Web Site: [www.formax.com](http://www.formax.com)

**LOCAL DEALER:**

## CONTINUOUS FORM DECOLLATOR



FD 524

The FD 524 decollator separates two-part carbonless or carbon interleaved forms in a single pass. Multi-part forms may be separated by processing them multiple times.

### TWO-PART DECOLLATOR

#### Specifications:

Variable Speed:	0 - 450 feet per minute
Form Size:	2.75" - 21" W x Up to 14" L
Power:	115 volts AC 50/60 Hz
Weight:	89 lbs.
Dimensions:	48" L x 29" W x 42.5" H
Features:	Variable speed, paper control rods for carbonless forms, carbon rewind spindle
Safety Certifications:	UL